
Comparisons of Experimental and Simulated Turbulence Quantities

Terry L. Rhodes
Electrical Engineering Department
University of California, Los Angeles



Collaborators

J.-N. Leboeuf	Physics Dept., UCLA, Los Angeles
R. Groebner	General Atomics, San Diego, CA., USA
E.J. Doyle	Electrical Engineering Dept., UCLA, Los Angeles
G. McKee	University Wisconsin Madison, WI., USA
J. Candy	General Atomics, San Diego, CA., USA


Today's presentation

- Current and near future turbulence diagnostics on DIII-D.
- Some mechanics of comparisons.
- Example of diagnostic issues using FIR scattering as well as illustrating new diagnostics coming on line.
- Data from correlation reflectometer system
 - Comparison to UCAN
 - Preliminary comparison to GYRO
 - Also new data from NSTX
- Some observations and issues from an experimentalist's perspective.

Current and near future DIII-D turbulence diagnostics


<u>Diagnostic</u>	<u>Example limitations</u>	<u>Measurements</u>
FIR scattering	Chord averaged	\tilde{n}, k_θ
PCI (phase contrast imaging)	Chord averaged	$\tilde{n}, \Delta r$
Reflectometry	Location is profile dependent	$\tilde{n}, \Delta r, k_\theta, V_\theta$
BES (beam emission spectroscopy)	Need NBI	$\tilde{n}, \Delta r, k_\theta, V_\theta$
ECE (electron cyclotron emission)	Long time average	$T_{\tilde{t}ilde}, k_\theta, V_\theta$
Langmuir probes	Edge plasma	$\tilde{n}, \phi_{\tilde{t}ilde}, T_{\tilde{t}ilde} \Gamma, Q, k_\theta, V_\theta$
Magnetic probes	Edge plasma	$B_{\tilde{t}ilde}, k_\parallel, k_\theta$
Polarimetry (future)	Chord averaged	$B_{\tilde{t}ilde}$
High-k scattering (future)	Under development	$\tilde{n}, k > 10 \text{ cm}^{-1}, k\rho_s > 1$

Mechanics of Comparisons




- Implement numerical diagnostics that simulate real world experimental measurements and analysis techniques.
 - Examples: local \tilde{n} wavenumber/frequency spectra, magnitude (e.g. via reflectometry, beam emission spectroscopy), chord averaged \tilde{n} with narrow k response (FIR scattering), local heat transport, etc.
- **Simulated diagnostics use similar localization (or lack thereof), wavenumber/frequency response, detection position within the plasma,**
 - Use similar data analysis techniques, including FFT's, correlation analysis, normalizations, etc.
- Work in this area ongoing and more recently includes
 - D. Ross, U. Texas, et al., compare BES, simulation
 - B. Nevins, LLNL - synthetic diagnostics

Example: FIR scattering




Scattering Spatial Response Function




- FIR scattering detects density fluctuations
- Observed wavenumber k_{obs} depends on viewing angle (probe wavenumber = k_0)
 $k_{\text{obs}} = 2 k_0 \sin(\theta/2)$.
- Spatial resolution depends on k_{obs} .
- Δk depends on beam size a ($\Delta k = 2/a$)

Initial 3-D design drawing of integrated high k system



Modification in approach to high k scattering



**Scattered radiation
with scattering angles
from 10 to 19 degrees.**

**Probes "k"s from ~10
to ~20cm⁻¹**

**Optical system can either use a
single lens and collect full range
of wavenumbers.**

or

**Smaller individual lenses can be
used to select different
individual "k"s.**

- Rather than adopting the concept outlined in a recent DoE proposal, UCLA plans to implement more of an incremental approach so that
 - (1) Believable data at high k might be obtained earlier
 - (2) This data would then guide future system design and lead to an improved system
 - (3) The modified system allows integration into the new vent and run schedule

High-k density fluctuation backscattering





Fig. 1. Backscattering geometries.



- M. Gilmore (UCLA but soon to be at UNM) proposing to measure high-k using combination of ECH waveguides and current reflectometry antennas.
- Depending upon geometry will be $k \sim 30\text{--}60 \text{ cm}^{-1}$
- Measurement location will initially be on high field side of tokamak.

Example: Correlation reflectometry




- Turbulence data obtained from correlation reflectometer- radial correlation length.
- Correlation length is a statistical quantity, independent of amplitude thus avoiding some potential calibration issues and making it good comparison quantity.
- Second advantage of system is ability to probe large region of plasma cross-section in many different regimes (Ohmic, L-mode, QDB, etc.)
- Representative cross-correlation shown.

Examine Δr from L-mode plasmas





- L-mode discharge - sawteeth avoided via early neutral beams.
- Radial profiles of density and temperatures at the time of interest.
- Plasma in a regime relevant to
 - trapped electron mode ($\rho < 0.9$),
 - collisionless drift wave ($0.9 < \rho < 1$),
 - ion temperature gradient (ITG) mode ($\rho < 1$).

Radial Correlation Length Decreases with Radius




- Δr are 5-10 times larger than ρ_s
 - but are of order poloidal $\rho_{\theta,s}$
- ion sound gyroradii
 - $\rho_s = (m_i T_e)^{1/2} / eB$
 - $\rho_{\theta,s} = (m_i T_e)^{1/2} / eB_\theta$
 - ρ_s important as enters into theoretical predictions of radial correlation lengths Δr .
- Indeterminacy of Δr scaling with $\rho_{\theta,s}$ or ρ_s is interesting and important question which we will return to later.

UCAN Turbulence Simulation Code





- Massively parallel, nonlinear, toroidal, 3D, global gyrokinetic particle-in-cell (PIC) code developed at UCLA [Sydora, '87] utilized.
- Cartesian coordinates covering whole plasma cross section (or as is numerically feasible).
- Circular cross-section.
- Electrostatic approximation is imposed throughout.
- Adiabatic electrons.
- The nonlinear δf method is applied to solve the gyrokinetic Vlasov-Poisson system of equations.
- Polynomial fits to experimental profiles (n_e , T_i , q , E_r) to set initial equilibrium.

Simulation Produces Similar Results When Zonal Flows Included





- Two different numerical runs shown - with/without zonal flows.
- Without zonal flows Δr are long, spanning most of 65 cm radius.
- With zonal flows Δr drop to near measured Δr in magnitude and radial behavior.
 - Δr reduction with zonal flow also observed in other simulations.
- Zonal flows clearly change turbulence characteristics and are necessary for agreement with experiment.

ρ^* scaling experiment -Preliminary!





- Reflectometer data in $5-10 \rho_s$ range.
- Reflectometer and BES data reasonably close given different radial positions.
 - Shots for reflectometer data not matched.
 - No comparable reflectometer data for 1T case.
- Radial variation?
 - Illustrates need for radial profiles from simulation.
- Illustrates experimental problems associated with comparisons - matching spatial location, times, ...

Compare experiment and GYRO for ρ^* scaling experiment -Preliminary!



- Reflectometer data in 5-10 ρ_s range.
- Reflectometer and BES data reasonably close given different radial positions.
 - Shots for reflectometer data not matched.
 - No comparable reflectometer data for 1T case.
- Radial variation?
 - Illustrates need for radial profiles from simulation.
- Illustrates experimental problems associated with comparisons - matching spatial location, times, ...
- GYRO - kinetic electrons, rotation, shaping, shafranov shift, profile variation, $\beta > 0$



Compare experiment and GYRO for ρ^* scaling experiment -Preliminary!



- Reflectometer data in 5-10 ρ_s range.
- Reflectometer and BES data reasonably close given different radial positions.
 - Shots for reflectometer data not matched.
 - No comparable reflectometer data for 1T case.
- Radial variation?
 - Illustrates need for radial profiles from simulation.
- Illustrates experimental problems associated with comparisons - matching spatial location, times, ...
- GYRO - kinetic electrons, rotation, shaping, shafranov shift, profile variation, $\beta > 0$

Example: NSTX correlation reflectometer data


Radial Correlation Lengths Vary With Magnetic Field for Fixed I_p/B_{tor} ("Constant q")




- Fixed line avg density, n_L
- B taken from EFIT01
- No apparent changes with NB source A vs. source C

Radial Correlation Lengths Scale with ρ_s at Fixed I_p/B_{tor} (“Constant q ”)

- $\Delta r \approx 6-7 \times \rho_s$, where $\rho_s \propto 1/|\underline{B}|$
- $\Delta r \approx 4-5 \times \rho_{s,\text{toroidal}}$, where
 $\rho_{s,\text{toroidal}} \propto 1/B_{\text{toroidal}}$
- $\Delta r \approx 3-4 \times \rho_{s,\text{poloidal}}$, where
 $\rho_{s,\text{poloidal}} \propto 1/B_z$ at the midplane





Normalized Correlation Lengths Decrease with B_{tor} at Fixed I_p (1 MA)





- Δr varies with $|B|$ (or B_{tor} on axis), but $\Delta r / \rho_s$ not constant
- scaling by $\rho_{s,\text{toroidal}}$, $\rho_{s,\text{poloidal}}$ show the same trend

Apparent Increase in Normalized Correlation Lengths with Increasing Line Density

- Fixed I_p (1 MA) and B_{tor} on axis (4.5 kG)
- T_e decreasing as \overline{nL} increases





Example: DIII-D Low and high density discharges show different confinement characteristics (Rettig APS 2000)




- Circular cross section plasmas used.
- Low and high n_e discharges showed different confinement as well as turbulence characteristics.
 - Energy confinement initially increases with density then saturates.

Low and high density discharges also show different turbulence characteristics (Rettig APS 2000)




- Appearance of low frequency density fluctuation at higher n_e .
- Poloidal propagation (from reflectometer) shows changes consistent with appearance of \tilde{n} propagating in ion diamagnetic drift direction.

Low density plasma did not go unstable in UCAN simulation due to lack of non-adiabatic electrons




Low density discharge

$$t = 6.8 \times 10^3 / \omega_{ci}$$



- Time history of electrostatic fluctuation energy shown above.
- Simulation with trapped electrons now goes unstable.
- Resulting instabilities looked like mix of TEM and ITG





High density discharge

Non-linear saturation


Low density case not unstable in previous UCAN simulation.

Example: High Performance Plasma (QDB Discharge)




- Quiescent double barrier (QDB) plasmas are high performance plasmas characterized by transport barriers in both edge and core.
- Compared to standard L-mode discharges QDB plasmas show substantial reduction in core electron and ion thermal diffusivities
- Results thought to be consistent with ExB velocity shear decorrelation of turbulence and resulting reduced transport.

Radial Correlation Lengths Shorter in QDB Plasmas




- QDB Δr below values normally seen in L-mode - but still larger than ρ_s .
- Departure from normal L-mode type scaling occurs most clearly for $r/a = 0.2-0.5$.
- Since Δr often related to transport step length this decrease in Δr is consistent with local decrease in transport levels.
- Simulation Δr similar to experimental data in magnitude and radial behavior.
- Large zonal flows generated in simulation, of order experimental ExB flows.
 - As much as 20 km/s compared to experimental 30 km/s.
- Without zonal flows simulated Δr very long, consistent with picture of shear induced Δr reduction.

Effect of reversed magnetic shear is weak in simulation




- QDB plasmas have weak negative central magnetic shear
- Simulation shows little difference between two cases.
- What are shortened Δr due to in simulation? Shaping, electrons dynamics, ...?

Example: Does Δr scale with ρ_θ or with ρ_s ?




- Uncertainty between Δr scaling with $\rho_{\theta,s}$ or $5-10 \rho_s$ was intriguing.
- Pointed to possible trapped particle effect via $\rho_{\theta,s}$.
- Also several analytic theories have $\rho_{\theta,s}$ dependence.
- Previously found $\Delta r \sim \rho_i$ (McKee, 2001).
 - Experiment was at constant q .
 - Results could be due to B or B_θ .
- Experiment to investigate rq,s scaling and to break indeterminacy.
- L-mode plasmas, varied B_θ via I_p .

Simulation Predicted No Strong Scaling With ρ_θ



- Prior to experiment simulations performed to predict Δr variation with ρ_θ .
- L-mode conditions, q value varied by factor of 4.
- Found no clear variation of Δr with ρ_θ - similar to experiment.
- In simulation, q also varied by changing major radius R (via $q=rB_z/RB_\theta$).
 - Some weak evidence of Δr variation observed, presumably due to major radius variation.
 - This effect will be numerically tested more fully in the future.

Correlation length not strongly dependent on ρ_θ



- Found no clear variation of Δr with change of ~ 1.8 in ρ_θ .
- \Rightarrow Scaling found previously was indeed with B_0 and ρ_s

Needs and questions

- **High-k simulations** - diagnostics coming on line, DIII-D, NSTX
- **Magnetic fluctuation simulations** ? - diagnostic planned, within 1-2 years
- **T_e fluctuation simulations** - measurements possibly next run period.
- **Shaping**
 - Affects QDB simulations on DIII-D?
 - NSTX simulations needed.
- **Electron dynamics** - clearly affects some results, QDB?.
- **Most measurements** are n_{tilde} , some $T_{e\text{tilde}}$, B_{tilde}
 - Code differences between n_{tilde} and ϕ_{tilde} ?

Observations and Issues

- “Qualitative vs quantitative”
 - Correlation lengths, spectral shapes, changes in \tilde{n} , fluxes, etc. with plasma parameters.
versus
 - Absolute \tilde{n} , fluxes, etc.
 - Is one class more appropriate or better than other?
- Multi-point vs single point
 - Agreement/disagreement in restricted radial range probably not enough.
 - Scalings with plasma parameters, e.g. non-dimensional scalings needed but again more than one radial position.

Observations and Issues

- Time vs space
 - **Experiments** have lots of time points, good statistics, limited spatial points.
 - **Simulations** with lots of spatial points, limited time
 - Can simulations utilize extra spatial points as proxy for time?
 - Similar to using increased number of time realizations in time series analysis.
- Fluxes vs diffusion coefficients
 - Fluxes (heat and particle) more directly related to experimental measurements.

Bookkeeping and small things that can take a lot of time

- **Common Definitions**

- RMS levels: $Y_{\text{RMS}}^2 = \langle [Y - \langle Y \rangle]^2 \rangle$ where $\langle \dots \rangle$ is a time average over an agreed upon time T.
- \tilde{n}/n , \tilde{T}/T , $\tilde{\phi}/T$ all normalized to local values of n and T, where the tilde ~ indicates an RMS value.
- Spectra $P_{YY}(f) = \Im(Y) \cdot \Im^*(Y)$ are power not amplitude.
- Correlation lengths: 1/2 power vs 1/e widths.

- **Input of experimental info, profiles into code**

- e.g. EFIT data, density, Te, velocity profiles
- Ease of input
- Error checking

Future Experimental Measurements

- n_{tilde} - Te_{tilde} phase?
- k_{parallel} ?
- more globally extended measurements of zonal flow?
- Others?